

EN 13229	Nordpeis AS	CE
Type: N27	Fuel (use only recommended fuel) Beech logs	Nominal heat output 9,0 kW
Thermal insulation	Lateral: 6 cm	Rear: 6 cm
	Base: 6 cm	Top: 6 cm
Efficiency: 80.8%	CO based on 13% O ₂ : 0.09%	Flue gas temperature 268 °C

Intermittent burning appliances

Double allocation is not acceptable

Read follow the manual

EN 13229	Nordpeis AS	CE
Type: N30	Fuel (use only recommended fuel) Beech logs	Nominal heat output 10,0 kW
Thermal insulation	Lateral: 6 cm	Rear: 6 cm
	Base: 6 cm	Top: 6 cm
Efficiency: 81.0%	CO based on 13% O ₂ : 0.07%	Flue gas temperature 285 °C

Intermittent burning appliances

Double allocation is not acceptable

Read follow the manual

EN 13240	Nordpeis AS	CE
Type: Malaga	Fuel (use only recommended fuel) Beech logs	Nominal heat output 10,0 kW
Distance	Lateral: 3 cm	Rear: flush to the
	Base: ---	Top: ---
Efficiency: 81.0%	CO based on 13% O ₂ : 0.07%	Flue gas temperature 285 °C

Intermittent burning appliances

Double allocation is not acceptable

Read follow the manual

EN 13240	Nordpeis AS	CE
Type: Barcelona	Fuel (use only recommended fuel) Beech logs	Nominal heat output 9,0 kW
Distance	Lateral: 3 cm	Rear: flush to the
	Base: ---	Top: ---
Efficiency: 80.8%	CO based on 13% O ₂ : 0.09%	Flue gas temperature 268 °C

Intermittent burning appliances

Double allocation is not acceptable

Read follow the manual